

ECCO



At ECCO, we appreciate just how dangerous the utility industry can be. And we're not just talking about installing and maintaining gas pipelines, underground sewer systems and overhead power lines. We are also talking about placing vehicles and technicians in harm's way at the side of busy roads while these tasks are carried out. Most utility vehicles operate at all hours of the day and night, through all kinds of weather. In fact, it is often the weather that necessitates utility crews to be out making repairs. Aside from the threat of inattentive drivers speeding by, the equipment installed on the vehicles including boom lifts, cranes, and cutting equipment also poses a significant risk to the operator. The likelihood of a reversing collision is also increased when large utility bodies limit rear visibility.


ECCO offers an extensive line of safety solutions that is ideally suited to utility vehicles. High-intensity LED warning lights give approaching drivers advanced notice of a hazard while our range of worklamps ensure that even in the lowest visibility conditions, operators can see clearly what they are doing. Finally ECCO's reversing safety solutions include back-up alarms to warn other road users and pedestrians of a reversing vehicle while our camera systems assist the driver in avoiding obstacles in their blind spots.



Read on to learn about specially selected products for utility trucks, large and small.



LIGHTBARS





12 Series VANTAGE

SAE Class | LED Lightbar



14 Series PXIDS

SAE Class I Modular LED Lightbar



21 Series

SAE Class I LED Lightbar



2000	1111		0000	THE S
54"	#12-00 C Amber T 16 LED V 12-24 A 7.2 ØSAE J84 (•)3 Year	S	California Tit	CE, R10






- 47" # 21-00005-E
 - C Amber
 - T 16 LEDs, 2 AL, 2 WL, 6 Module Safety Director
 - **V** 12
 - **A** 12.0
 - Ø SAE J845 Class I, Cal. Title 13
 - 🕒 5 Year



MINIBARS







5585A PEFLE×° C Amber V 12-24 A 5.1 X 4 Bolt Ø SAE J845 Class I, CE, R10, IP65 ⊕ 3 Year

AVAILABLE COLORS Amber, Blue, Clear, Green, Red & Amber/Clear (MG models amber illumination only)





- # 5590A REFLEX
- C Amber
- **V** 12-24
- A 6.0
- 🗙 4 Bolt
- SAE J845 Class I California Title 13, CE, R10, IP65
- 🕒 3 Year

AVAILABLE COLORS

Amber, Blue, Clear, Green & Red (MG models amber & amber/clear only)





5587A PEFLE× C Amber V 12-24 A 5.1 X 4 Bolt Ø SAE J845 Class I, CE, R10, IP65 ⊕ 3 Year

AVAILABLE COLORS Amber, Clear, Amber/Clear (MG models amber & amber/clear only)



- # 5597A REFLEX C Amber
- V 12-24
- A 6.0
- 🗙 4 Bolt
- SAE J845 Class I, California Title 13,
- CE, R10, IP65
- 🕒 3 Year

AVAILABLE COLORS


Amber, Clear, Amber/Clear (MG models amber & amber/clear only)



5580A REFLEX
Amber
12-24
2.7
4 Bolt
SAE J845 Class II, CE, R10, IP65
3 Year

AVAILABLE COLORS Amber

BEACONS









7950A

🗙 3 Bolt / 1" Pipe

C Amber

V 12-48

2 Year

A 1.3

7945A C Amber V 12-48 A 1.3 X 3 Bolt / 1" Pipe SAE J845 Class II, CE, R10 🕒 2 Year



CA models = clear lens / amber illumination | CC models = clear lens / clear illumination



7965A C Amber V 12-24 A 3.6 X 3 Bolt / 1" Pipe Ø SAE J845 Class II, CE, R10 SAE J845 Class I, CE, R10 2 Year



7970A C Amber V 12-24 A 3.6 X 3 Bolt / 1" Pipe Ø SAE J845 Class I, CE, R10 2 Year



7975A **T** Severe Vibration C Amber V 12-24 A 3.6 X 3 Bolt / 1" Pipe Ø SAE J845 Class I, CE, R10



7980A **T** Severe Vibration C Amber V 12-24

- A 3.6
- X 3 Bolt / 1" Pipe Ø SAE J845 Class I, CE, R10
- 4 2 Year

EB7180A





- # EB7180A-VM
- C Amber
- **V** 12-24
- A 6.2
- X Vacuum-Magnet
- R10, IP55, AMECA
- (3 Year





- X 3 Bolt / 1" Pipe
- SAE J845 Class I, Cal. Title 13,
- R10, IP55, AMECA 3 Year



EB7185A-VM Dual-color

C Amber

4 2 Year


- V 12-24
- A 8.6
- X Vacuum-Magnet
- Ø SAE J845 Class I, Cal. Title 13, R10, IP55, AMECA
- 3 Year

AVAILABLE COLORS (EB7180 / EB7185)

Amber, Clear/Amber/Amber, Clear/Amber/Clear & Clear/Clear

CAA models = clear lens / amber illumination | CAC models = clear lens / amber and clear illumination | CCC models = clear lens / clear illumination

DIRECTIONAL WARNING





UTILITY



- **# ED3701A** Solid- or split-color
- C Amber
- **v** 12-24
- A 0.8
- X 2 Bolt
- SAE J595 Class I California Title 13, R65, R10
- 🕒 3 Year

AVAILABLE COLORS

Amber, Blue, Clear, Green, Red, Amber/Blue, Amber/Clear, Amber/Green, Amber/Red, Blue/Clear, Red/Blue & Red/Clear





- # ED3706A Solid- or split-color
- C Amber
- V 12-24
- A 0.9
- Multi-Mount (surface, tilt bracket, self-adhesive, edge)
- SAE J595 Class I, California Title 13, R65, R10, IP67
 3 Year

AVAILABLE COLORS

Amber, Blue, Clear, Green, Red, Amber/Blue, Amber/Clear, Amber/Green, Amber/Red, Red/Blue





Solid- or split-color # 3811A C Amber

- ▼ 12-24 ▲ 0.4
 - X 2 Bolt Grommet SAE J595 Class I SAE J595 Class I CE, R10 CE, R10

4 3 Year

AVAILABLE COLORS Amber, Blue, Clear & Red

9014A (Hide-A-LER)





3861A

Amber

12-24

3 Year

0.4

#	3510A	
С	Amber	
V	12-24	
Α	0.75	
×	2 Bolt	
~		

SAE J595 Class I
 California Title 13, CE, R10
 SAE J5

(5 Year

AVAILABLE COLORS Amber, Blue, Clear, Green & Red

nber, Blue, Clear, Green & Red Amber, Blue, Cl

C Amber

v 12-24

🗙 2 Bolt

Ø SAE J595 Class I, R10

A 0.5



3703A / 3704A / 3705A



ED3702AC Dual-color

- C Amber/Clear V 12-24 A 0.6 X 2 Bolt
- SAE J595 Class I
- California Title 13, R65, R10

AVAILABLE COLORS

Amber/Blue, Amber/Clear, Amber/Green, Amber/Red, Blue/Clear, Red/Blue & Red/Clear



V 12-24

R65, R10

AVAILABLE COLORS

A 0.9

ED3712AC Dual-color C Amber/Clear

self-adhesive, edge)

X Multi-Mount (surface, tilt bracket,

Amber/Blue, Amber/Clear, Amber/Green,

Amber/Red, Blue/Clear, Red/Blue & Red/Clear


- C Amber T 6 LEDs
- 1 Head
- V 12-24
- A 0.9
- SAE J595 Class I, California Title 13, X 2 Bolt R65, R10
 CE, R10, IP67

AVAILABLE COLORS

Amber, Blue, Clear & Red



WORKLAMPS









600 Raw, 600 Effective Flood **O** CE. R10. IP67 3 Year





EW2411

Ø IP67, CE, R10

L 1000 Raw, 900 Effective

V 12-24

Flood

🕒 3 Year

A 1.3



E92006 **V** 12-24 A 1.3 L 1300 Raw, 1200 Effective Flood 🛛 CE 🕒 2 Year



EW2421 V 12-24 **A** 2 L 2400 Raw, 2200 Effective Flood **Ø** IP67, CE

🕒 3 Year



EW2431 V 12-24

- A 3.1
- L 2600 Raw, 2100 Effective Flood
- Ø IP67, CE
- 🕒 3 Year



EW2450

L 1300 Raw, 1100 Effective

V 12-24

A 2.2

🥭 Spot

🕒 3 Year

Ø ĊE



(3 Year






E92007 V 12-24

A 0.7

- L 750 Raw, 700 Effective
- 🥒 Flood 🖉 CE
- C 2 Year

UTILITY BARS







EVV3108-F
T 8" Single Row
V 12-24
A 1.9
L 1100 Raw, 1000 Effective

- 🥒 Flood
- 🧭 IP67, R10
- 🕒 3 Year



EW3114 T 14" Single Row V 12-24 A 5.7 L 3350 Raw, 2600 Effective ✓ Flood / Spot Combo Ø IP67, R10

• 167, K






EW3214

- T 14" Double Row
- V 12-24
- A 9.3
- L 6700 Raw, 4800 Effective
- Flood / Spot Combo
- Ø IP67, R10
- 🕒 3 Year

INTERIOR LIGHTING



Recommended installation location options



Strip Lighting

EW0116
T 18 LED
V 12
A 0.4
1 350 Raw, 350 Effective
Flood
🧭 CE, RoHS, IP65
🕒 3 Year

O CE, R10, RoHS, IP64

🕒 3 Year

OCE, R10, RoHS, IP64

🕒 3 Year

24"
EW0117
T 36 LED
v 12
A 0.7
L 700 Raw, 700 Effective
🥟 Flood
🧭 CE, RoHS, IP65
🕒 3 Year

ACCESSORIES

O CE, RoHS

3 Year

EZO120 PIR Motion Sensor - 110° cone, adjustable sensitivity (automatically activates light when human movement is detected)




Interior Lighting CONNECT 14" MODULAR FROST 4.5" CLEAR 7" CLEAR 5.5" MULTIPLE UNITS TOGETHER 📺 🌗 # EW0310 # EW0320 # EW0351 **EW0200** T 4 LED T 8 LED **T** 16 LED 72 LED Τ. V 12-24 **V** 12-24 **V** 12 Multiple lengths available **V** 12-24 A 0.1 A 0.1 A 0.5 0.4 Α L 100 Raw, 100 Effective L 200 Raw, 200 Effective L 300 Raw, 250 Effective L 400 Raw, 400 Effective Flood Flood Flood Flood Amplia OCE, RoHS **O**CE, RoHS, **O** CE. RoHS Ø CE, RoHS 3 Year 🕒 3 Year 3 Year 3 Year 5.5″ 12" 13″ 22″ # EW0700 # EW0701 # EW0400 # EW0401 T 6 LED T 12 LED T 10 LED T 22 LED V 12-24 **V** 12-24 **V** 12-24 **V** 12-24 A 0.4 A 0.5 A 0.9 A 0.7 L 200 Raw, 200 Effective L 450 Raw, 450 Effective ▲ 400 Raw, 350 Effective L 1250 Raw, 1200 Effective Flood Flood Flood Flood

OCE, RoHS

3 Year

REVERSING SAFETY





Back-Up Alarms



510	Ħ	530
SRC*	Т	SRC*
12	V	12-24
97	dB(A)	102
0.2	Α	1.0
2 Bolt	×	2 Bolt
SAE J994 Type C, CE,	Ø	SAE J994 Type F
R10, UL, AMECA, IP65		CE, R10, UL, IP65
2 Year	⊕	2 Year
	SRC* 12 97 0.2 2 Bolt SAE J994 Type C, CE, R10, UL, AMECA, IP65	SRC* T 12 V 97 dB(A) 0.2 A 2 Bolt X SAE J994 Type C, CE, Ø R10, UL, AMECA, IP65 Ø

EDO

	# SA950 MART
	V 12-24
	dB(A) 82-102
	A 0.4
	🗙 2 Bolt
	🧭 CE, R10, UL, IP65
F	🕒 2 Year



SA955 MART **V** 12-24 dB(A) 82-102 A 0.4 🗙 Grommet O CE, R10 2 Year

Multi-Frequency Alarm



- # EA5200 MULTI **V** 12-24 dB(A) 97
- A 1.0 🗙 2 Bolt
- SAE J994 Type C CE, R10, AMECA 🕒 2 Year

Camera Systems



EC5603-K Gemineye 5.6" LCD color system Touchscreen menu control CMOS 11 LED infrared camera Includes monitor sunshade Three camera expandable One year warranty



EC5605-WK Gemineye 5.6" LCD color system 2.4 GHz digital wireless system Touchscreen menu control CMOS 11 LED infrared camera 2 Bolt Includes monitor sunshade Four camera expandable One year warranty



K7000B Gemineye 7" LCD color system CMOS 18 LED infrared camera Includes monitor sunshade Two camera expandable One year warranty



EC7000-OK Gemineye 7" Quad view LCD color system Quad view, split screen CMOS 11 LED infrared camera Four camera expandable One year warranty



EC7003-K Gemineye 7" LCD color system Touchscreen menu control CMOS 11 LED infrared camera Includes monitor sunshade Three camera expandable One year warranty



Worldwide leader in commercial and emergency vehicle warning and safety products

www.eccosafetygroup.com



833 West Diamond Street, Boise, Idaho 83705 (800) 635-5900 | sales@eccolink.com | www.eccolink.com

A COLORING

ECCO

A Division of ESG | www.eccosafetygroup.com



© 2016 Electronic Controls Company UTILITYBROCHURE (916 - Digital)